

# 115E-2 Ethernet Networking I/O and Gateway

## Configurable and scalable multiple I/O node for industrial applications



### Description

The ELPRO 115E-2 Ethernet Networking I/O and Gateway is a multiple I/O node that extends communications to sensors and actuators in local, remote, or difficult to reach locations. Designed to work with wired and wireless devices, the ELPRO 115E-2 is capable of providing IP-based I/O across sprawling industrial environments typical of industrial applications.

The 115E-2 can serve as an end node or network gateway and is scalable to thousands of nodes. Gather-scatter and block mapping technology offers the efficient use of network resources, allowing point-to-point transfer of process signal within complex monitoring and control systems. Integrated Modbus® server capability allows further I/O expansion through the use of ELPRO 115S expansion modules.



Powering Business Worldwide

### Features

- Modbus RTU and TCP support
- Serial client/server/multicast Modbus TCP to RTU gateway
- Configurable digital, pulse, and analog I/O to 14-bit resolution
- Gather-scatter and block mapping
- 10/100BaseT IEEE 802.3 Ethernet
- Network diagnostics and configuration

### Applications

- Water and wastewater systems
- Oil and gas production and distribution
- Pipeline monitoring and leak detection
- Mining operations infrastructure

### Specifications

SPECIFICATION	DESCRIPTION
<b>Input and Output</b>	
Digital input	8 digital inputs (shared with outputs), 1–4 configurable as PI or PO On-state voltage: <2.1 Vdc Wetting current: 5 mA Max. I/P pulse rate DI 1/2: 50 kHz, DI 3/4: 1 kHz Max. I/P pulse width DI 1/2: 10 µsec, PI 3/4: 0.2 msec
Digital output	8 digital outputs (shared with inputs), 1–4 configurable as PI or PO Load voltage, DO max. 30 Vdc Load current, DO max. 200 mA Max O/P pulse rate, PO max. rate 1 kHz
Analog input	4 AI (2 differential, 2 single ended) Current range: 0–24 mA Current resolution: 14 bits Accuracy (current): 0.1% Voltage input range: AI 1/2: 0–25V, AI 3/4: 0–5V Voltage resolution: 14 bits Accuracy (voltage): 0.1%
Analog output	2 AO (sourcing) Current range: 0–24 mA Current resolution: 13 bits Accuracy (current): 0.1%
<b>Ethernet Port</b>	
Ethernet port	10/100BaseT, RJ-45 connector, IEEE 802.3
Link activity	Link, 100BaseT via LED
<b>Serial Port</b>	
RS-232	EIA-562 (RJ-45 connector)
RS-485	2-pin terminal block, non-isolated
Data rate (bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400
Serial settings	7/8 data bits, stop/start/parity (configurable)
<b>Protocols and Configuration</b>	
System address	1 to 31-character text string
Protocols supported	TCP/IP, UDP, HTTP, FTP, TFTP, TELNET, Modbus, Modbus TCP

## Specifications (continued)

SPECIFICATION	DESCRIPTION
User configuration	All user-configurable parameters via HTTPS
Configurable parameters	Unit details, I/O mappings and parameters (for more, refer to the user manual) Modbus TCP/ RTU gateway Embedded modbus master/slave for I/O transfer
Security	Secure HTTP protocol
<b>LED Indication and Diagnostics</b>	
LED indication	Power/OK, RS-232, RS-485, digital I/O, analog I/O status
Reported diagnostics	Connectivity information/statistics, system log file
Network management	Optional Network Management System (NMS)
<b>Compliance</b>	
EMC	FCC Part 15, EN 55022, AS 3548, CE
Hazardous area	UL/CSA Class I, Division 2; ATEX; IECEx Na IIC - PENDING
Safety	IEC 60950 (RoHS compliant)
UL	UL listed
<b>Power Supply</b>	
Nominal supply	10.8–30 Vdc, under/over voltage protection
Average current draw	220 mA @ 12V (idle), 110 mA @ 24V (idle)
<b>General</b>	
Size	5.91" x 7.09" x 1.38" (180 mm x 150 mm x 35 mm)
Housing	IP20-rated high-density thermoplastic
Mounting	DIN rail
Terminal blocks	Removable, max. conductor 12 AWG 0.1 in. <sup>2</sup> (2.5 mm <sup>2</sup> )
Temperature rating	–40 to +140°F (–40 to +60°C)
Humidity rating	0–99% RH noncondensing
Weight	1.1 lb (0.5 kg)

**Note:** Specifications are subject to change.

## Ordering

PRODUCT CODE	DESCRIPTION
115E-2	Ethernet I/O

## Accessories

PRODUCT CODE	DESCRIPTION	DATA SHEET
<b>Interface</b>		
915U-TCADP	T-type TCP thermocouple adapter that uses two analog inputs and two analog outputs	TD032088EN
915U-LOG	Data logging feature key	TD032090EN
<b>Cables</b>		
ETH-C5A	Ethernet cable, 6' (1.8m), direct, RJ-45 to RJ-45	TD032024EN
SER-RJ45	Configuration cable, RS-232 serial, DB-9 female to RJ-45	TD032027EN
<b>Surge Diverters</b>		
MA15D1SI/D2SI	Power supply surge diverter, 110 Vac/15A or 240 Vac/15A	TD032029EN
IOP32D	Signal surge diverter, 2 x 2-wire/1 x 4-wire	TD032032EN
<b>Power Supplies</b>		
PS-DINAC-12DC-OK	DIN rail power supply, 100–250 Vac, 12 Vdc/2.5A	TD032033EN
PSG60E	DIN rail power supply, 85–264 Vac, 24 Vdc/2.5A	TD032034EN

**Note:** Additional accessories are available for this product, including antennas, cables, and mounting brackets. Refer to our Web site for details.

**Eaton's wireless business**  
www.eaton.com/wireless

North America & Latin America  
5735 W. Las Positas Suite 100  
Pleasanton, CA 94588  
United States  
Telephone: +1 925 924 8500

Australia, New Zealand  
9/12 Billabong Street  
Stafford Queensland 4053  
Australia  
Telephone: +61 7 3352 8600

China  
955 Shengli Road  
East Area of Zhangjiang High-Tech Park  
Shanghai, 201201  
China  
Telephone: +86 21 2899 3600

Southeast Asia  
2 Serangoon North Avenue 5  
# 06-01 Fu Yu Building, 554911  
Singapore  
Telephone: +65 6645 9888

Europe  
Hein-Moeller-Straße 7-11  
53115 Bonn, Germany  
Telephone: +49 (0) 180 5223822



WWW.SpotcomLtd.co.uk  
Wireless Solutions and Support Services.

**Andrew Iain Spottiswood.**

[Andrew@SpotcomLtd.co.uk](mailto:Andrew@SpotcomLtd.co.uk)

+44 (0)7787 522704

Registered Office:- 20-22 Wenlock Road, London N1 7GU.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

© 2014 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. TD032097EN  
July 2014

Eaton is a registered trademark.

All other trademarks are property of their respective owners.